

## B-500Ti-2

## Typology: LABORATORY MICROSCOPE

## **Description:**

Laboratory microscope for routine and research applications. Dye-cast frame, with high stability and ergonomy, for transmitted light observation.

Illumination	Light source type X-LED³ with white LED; light intensity control using a knob on left side of the frame.  LED power 3W, comparable to an halogen bulb 50W.  Color temperature: 6300K  LED average life time approx. 50.000h.  The light exit can be used as a filter holder for additional filters (blue, yellow, frosted).  Voltage: 110/230Vac, 50/60Hz, 0,4/0,8A; Fuse: T3.15A 250V  Max power required: 7W
<b>Observation Modes</b>	Brightfield
Focusing	Coaxial coarse and fine focusing mechanism (graduated, 0.002mm) with upper stop, to prevent the contact between objective and specimen.  Adjustable tension of coarse focusing knob.
Stage	Double layer with mechanical sliding stage, size 175x145mm, X-Y movement range 76x52, specimen holder for two slides.  Vernier scale on the two axes, accuracy 0,1 mm.
Nosepiece	Quintuple revolving nosepiece, rotation on ball bearings.
Head	Trinocular observation head (main head) and binocular (discussion head), inclined 30° and rotatable 360°.  Diopter adjustment on left eyepiece. Interpupillary adjustment 55-75 mm.  Multi-viewing device (1 observer simultaneous with the main observer).  Discussion LED pointer with 3 selectable colors (red, green, blue) and intensity adjustment.
Eyepieces	Widefield eyepieces WF10X with field number 22 (on main head) and field number 20 (on discussion heads).
Objectives	Infinity corrected optical system IOS (Infinity Optical System).  Plan-achromatic objectives infinity corrected, made by following objectives:  -) Plan-achromatic IOS 4X, A.N. 0.10, W.D. 11.9 mm  -) Plan-achromatic IOS 10X, A.N. 0.25, W.D. 12.1 mm  -) Plan-achromatic IOS 40X, A.N. 0.65, W.D. 0.36 mm  -) Plan-achromatic IOS 100X, A.N. 1,25, W.D. 0.18 mm (oil immersion)  All objectives are treated with an anti-fungus treatment.
Condenser	Swing-out type, N.A.0,9 with centering system.
Dimensions	Main body:         HEIGHT:       420 mm         WIDTH:       250 mm         DEPTH:       290 mm         WEIGHT:       8 kg         Overall dimensions:       WIDTH:         WBIGHT:       12 kg
Accessories	Instruction manual and dust cover included.